

X-PAINT

X-Paint Metal

Description: Water-based metal paint that can be applied directly over rust

Color: White, Anthracite, Green, Black, Metallic Grey, Gold, Bronze, Sky Blue

Gloss: Glossy

Type: Water-based

General Features:

- 3-in-1: Rust Inhibitor + Primer + Topcoat
- Resistant to sunlight (UV) and other outdoor conditions
- High corrosion resistance
- Odorless
- High hiding power
- Ready to use

Packaging Size: 0,75 L., 2,5 L., 15 L.

Where to Use:

- All types of iron, aluminum, and metal surfaces
- Balcony railings
- Garden furniture
- Wrought iron
- Doors, window and window grilles

Product Data:

Solid Content (% weight):	52,97 ± 1
Viscosity (DIN8, 20°C):	28'' ± 2
Density (g/cm ³):	1,21 ± 0,02
VOC (g/L):	52
Application Method:	Brush, roller or spray gun (2,5-3 mm nozzle, minimum 3atm pressure)
Shelf Life (5-35°C):	2 years for unopened can
Number of Coats:	2 coats
Coverage (m ² /L):	10 m ² /L with 1 coat
Drying Time (at 20°C and 40-65% relative humidity):	Dust Free: 15 minutes Touch Dry: 30 minutes Recoat: 1,5-2 hours Complete Dry: 12 hours
Thinning:	Ready to use, does not require thinning.

X-PAINT

Surface Preparation:

- **New Metal Surfaces:**
 - Clean the surface thoroughly, removing all dirt, oil, and dust. On oily surfaces, it is recommended to clean with soapy water before application.
 - On glossy and smooth metal surfaces, lightly sand the surface with an appropriate abrasive material to ensure maximum adhesion.
- **Coated Metal Surfaces:**
 - Loose, blistered paint and rust layers should be cleaned, and if necessary, the surface should be lightly sanded with an appropriate abrasive material and wiped with cellulose thinner. Also, ensure the surface is free from all dirt, oil, salt, and dust. On oily surfaces, it is recommended to clean with soapy water before application.
 - On glossy and smooth metal surfaces, lightly sand the surface with an appropriate abrasive material to ensure maximum adhesion.

Application:

- The product is ready to use and does not require thinning.
- Stir the product thoroughly before use and check its homogeneity. Repeat this process during the application.
- Apply the product in 2 coats by brush, roller or spray gun (2,5-3 mm nozzle, min. 3 atm pressure) and wait 1,5-2 hours between coats.
- Wait 12 hours for complete dry.

Instructions:

- FOR EXTERIOR AND INTERIOR USE.
- Keep product closed when not in use.
- The general application temperature of the product is between 15°C to 25°C at a relative humidity range of 40-65%.
- The product should be protected from freezing and stored at temperatures between 5°C to 35°C.
- Painting tools should be cleaned with soap and plenty of warm water after application.

Safety Precautions:

- KEEP OUT OF REACH OF CHILDREN.
- Do not transfer contents to other containers for storage.
- Do not use empty cans for other purposes.
- Avoid contact with eyes and skin.
- Wash hands after using.
- FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.
- Dispose of contents/cans in accordance with national regulations.
- Please refer to the Safety Data Sheet (SDS) of the product for health and safety information.